SKG-IKOB PRODUCTCERTIFICATE 625.313.02

Date of issue: 08-03-2018





Certificate holder

Rav-Bariach (8) Industries Ltd.

Haofe St. 31

IL-78780 Ashkelon

T: +972 (0)867 949 14

E: export@rav-bariach.com

I: http://www.rb-doors.com

Declaration of SKG-IKOB

This certificate has been issued on the basis of BRL 3104 in accordance with the SKG-IKOB Regulations for Attestation, Certification and Inspection.

SKG-IKOB declares that the by or on behalf of the certificate owner produced building hardware product:

euro profile cylinder with non lockable knob

delivered under logo / brand:

KEYLOCX

delivered under type- and / or article number:

NE000206951, NE000206021

meets class 3 STER according BRL 3104 and NEN 5089: 2009 if the product is indelibly marked with the SKG mark, as shown above.

For SKG-IKOB

ir. H.A.J. van Dartel Certification manager

Verify at www.sterrenwijzer.nl if this certificate is still valid and actual. This certificate contains 2 pages.

SKG-IKOB Certificatie Poppenbouwing 56 4191 NZ Geldermalsen

Postbus 202 4190 CE Geldermalsen

T 088-2440100 info@skgikob.nl www.skgikob.nl

SKG-IKOB PRODUCTCERTIFICATE

Rav-Bariach (8) Industries Ltd.

Number: 625.313.02 page 2 of 2

PRODUCT TYPE 1. PRODUCT cylinder

euro profile cylinder with non lockable knob

2. TECHNICAL SPECIFICATION

Operating: Mechanical operation Construction: double, with knob System: horizontal key profile

1 row of 7 mechanical operated detainers,

of which 1 is magnetically operated

Material: cylinder body: brass with various coatings

Dimension: 17 mm profile

from 31 mm, 33 mm, 35 mm, 38 mm, and futher in

various extensions per 5 mm

Fixing: 1 steel bolt M5, lenght . backset + 10 mm

in combination with cylinder mortice locks and security furniture. Intended use:

Pay Attention!

This cylinder achieves only the SKG-star rating if a door element (including side window), wherein at least

P4A glass has been applied, OR

in a door element (including side window) with a

section filling without a view on the knob.

A wooden door element (including side window) with a view to the "standard" turning knob, should be provided with

a SKG (V) certified anti-drill / manipulation device.

3. DELIVERY

The delivery includes an installation instruction:

Versie 01 - 25-03-15

4. PERFORMANCES

A euro profile cylinder with non lockable knob according this certificate fulfils the relevant requirements of BRL 3104.

A window- or door set, in which this euro profile cylinder with non lockable knob is installed according the installation instructions of the certificate holder meets at least burglar resistance class (RC) 3 of NEN 5096 and EN 1627, if:

the façade element or the (profile-)system from which the element is manufactured is delivered under a (KOMO-)quality approval with respect to the aspect burglar resistance, in which the actual window or door type is admitted and the herein mentioned conditions are

A window or door, in existing buildings, in which this euro profile cylinder with non lockable knob is installed according the installation instructions of the certificate holder, meets the requirements of the Police Mark Save Housing (PKVW) - Existing Building, if:

the other aspects of the façade element also comply with the applicable PKVW Protection directive (publication CCV).